



## THICK-FILM/ MORTAR PUMPS 410.09 / 600.12

- Operator friendly
- Quick to clean
- Solvent flushing possible
- Robust design
- High flow speed
- Low wear



## WIWA MORTAR PUMPS 410.09 / 600.12

TECHNICAL DATA	WIWA 410.09	WIWA 600.12
Order-No.	0653609	0652595
Pressure Ratio	9:1	12:1
Max. Fluid Pressure	72 bar (1044 psi)	96 bar (1392 psi)
Output per cycl	410 cm <sup>3</sup> (14 (fl.oz))	600 cm <sup>3</sup> (20 (fl.oz))
Output at 60 Cycles	24,6 ltr. (6.5 gal.)	36 ltr. (9.59 gal.)
Air Motor Plate Diameter	140 mm (5.5 in.)	200 mm (8 in.)
Stroke Length	120 mm (4.7 in.)	120 mm (4.7 in.)
Max. Inbound Air Pressure	8 bar (116 psi)	8 bar (116 psi)
Min. Recommended Air Compressor Rating	3000 ltr./min (100 cfm)	3000 ltr./min (100 cfm)
Inbound Air Port (BSPP)	1/2"	1"
Inbound Fluid Fitting (BSPP)	2"	2"
Outbound Fluid Port (BSPP)	1"	1"
Accessory kit	Order-No.: 0653594	Order-No.: 0653594

### ZUBEHÖR



Pneumatic thick-film material agitator can be directly driven via the pump. Order-No.: 0652214

The **WIWA series 410.09 and 600.12** is perfectly suitable for the application of epoxy and water based thick-film materials and mortars, such as cement mortar, cement-bound fire protection materials, cement slurry and filled vinyl esters. In contrast to screw pumps, WIWA thick-film pumps can be flushed and cleaned with diluting agents. The pump is therefore also first choice when it comes to the transfer of epoxy based materials. Due to the use of quick release couplings the material pumps, which consist of only a few parts, can be quickly disassembled, cleaned and reassembled, which is highly beneficial with short processing times, which are quite common today. The feed funnel can also be simply removed. With this quick maintenance the downtimes, especially in construction site applications, can be reduced considerably. These large capacity pumps are designed with extra large flow passages, and due to the slow pumping speed only suffer very low wear, even when transferring high amounts of material.



Spray pipe with air atomizer



Complete system

#### Fields of application:

- Decks on ships and ferries
- Concrete and building sanitation
- Sealing of cellars (basements)
- Fire protection

#### The basic equipment consists of:

- Pump with carriage
- Quick release couplings
- 25 l (6.5 Gal) funnel with cover

#### The accessory kit consists of:

- 10.5 m (35') hose package in a protective hose
- Spray pipe with air atomizer
- 8.5 mm (5/16") nozzle (other nozzle sizes on request)

Headquarters and Production

**WIWA** Wilhelm Wagner GmbH & Co. KG  
Gewerbestraße 1-3  
35633 Lahnu, Germany

Tel. +49(0)64 41/60 9-0  
Fax +49(0)64 41/60 9-50

info@wiwa.de  
www.wiwa.de

WIWA Partnership USA

**WIWA** LP  
3734A Cook Boulevard  
Chesapeake, VA 23323, USA

Tel. +1-757-436-2223  
Fax +1-757-436-2103  
Toll Free +1-866-661-2139

sales@wiwalp.com • www.wiwa.com

WIWA Subsidiary China

**WIWA** Taicang Co., Ltd.  
Add: No. 87 East Suzhou Rd., Taicang city,  
Jiangsu province 215400, P. R. China

Tel. +86-512-5354 8858  
Fax +86-512-5354 8859

info@wiwa-china.com  
www.wiwa-china.com